



Servoväxel

Pris avser billigaste utförande

- Hög verkningsgrad
- Rakskurna drev
- Låg vikt
- Enkel montering



En kompakt serie enklare vinkelväxlar med rakskurna drev.
Växelhuset i stål med gavlar i aluminium håller nere både produktens vikt och pris.

IP-klass	IP65
Livslängd	20000 hr
Omgivningstemperatur	0° C~ 90° C
Utväxling	3:1-100:1

Technical drawings of the motor assembly showing front, side, and top views with dimensions:

- Front View:** Shows a circular motor housing with a diameter of 125. The mounting flange has a diameter of 80. The motor body has a diameter of 60. The mounting flange has a thickness of 10. The motor body has a length of 100. The mounting flange has a diameter of 80. The motor body has a diameter of 60. The mounting flange has a thickness of 10. The motor body has a length of 100.
- Side View:** Shows the motor assembly with a shaft diameter of 10. The motor body has a length of 100. The mounting flange has a diameter of 80. The motor body has a diameter of 60. The mounting flange has a thickness of 10. The motor body has a length of 100.
- Top View:** Shows the motor assembly with a shaft diameter of 10. The motor body has a length of 100. The mounting flange has a diameter of 80. The motor body has a diameter of 60. The mounting flange has a thickness of 10. The motor body has a length of 100.